



Illustration	Type	Description	Q-Cut 2516
	Q-CUT 2516	Effective cutting area: 2500mm *1600mm. High precision weld frame;Fixed working surface; Vacuum pump control sysytem; Electric Motor,Rail,cutting cusion; Control system	✓
	Tangent Knife(standard)	Universal Cutting Tool, used for through-cutting materials with thinkness up to 5mm, fast speed and low cost.	✓
	Creasing Tool(standard)	Make creasing on boards to make carton / box	✓
	Desk Table (Work station)	Can put the computer and tools (only desk, without computer)	✓
	Safety Device	Make the machine work in a safety environment.	✓
	CNC Router	300Watt NSK Japan Motor, cut Acyric, Forex, MDF, PVC foam, Di-bond.	✓
	Tool Module POT air setup	Two Tool Module to change the cutting tools Suitable for router, POT, EOT, UCT and other options.	✓
	Electric Oscillating Tool(EOT)	The Electrical Oscillating Tool is super suitable for cutting the material of medium density. Used for cutting KT board, cardboard, corrugated board, PVC, leather,etc	✓
	Kiss Cut	Half-cutting, mainly used for cutting film, sticker, vinyl, etc	✓
	Rail	THK Japanese rails	✓
	Vaccum Cleaner	Festool Vaccum Cleaner	✓
	CCD Camera Registration System(for sheet material)	Accurate registration of the data for the cutting material, registration accuracy is 0.1mm, for contour cutting on printedmaterials.	✓
	Auto Conveyor System	Crawler type conveyor belt, can realize automatic feeding, continuous cutting.Netherland imported belt.	✓
	Material Loading Device	The fabrics rolls can be loaded (less than 200KG), convenient automatic material feeding and manual material pulling; Customizable.	✓
TotalPrice			